



Food Safe Materials

Material	Max Operating Temp.	FDA/USDA
Acetal Copolymer: Natural	180°	X
Acetal Homopolymer (Delrin): Natural	180°	X
HDPE: Natural	180°	X
Polypropylene: Natural	180°	X
UHMW-PE: Natural	180°	X
UHMW-PE (LubX C and LubX CV): Natural	180°	X
Nylon 6: Natural	200°	X
Nylon 6/6: Natural	210°	X
PETG (Vivak): Clear	210°	X
PET (Ertalyte): Natural	210°	X
Lubricated PBT (Hydex 4101L®): Natural	221°	X
PBT (Hydex 4101): Natural	221°	X
Polycarbonate FG: Clear*	250°	X
Polysulfone (Tecason): Natural*	285°	X
PVDF (Kynar®): Natural	290°	X
PEI (Ultem): Natural	340°	X
PEEK: Natural	480°	X
PTFE (Teflon): Natural	500°	X

*Must Specify FDA Grade

Disclaimer: All trademarks and service marks are property of their respective manufacturers. All statements, technical information and recommendations contained herein are presented in good faith, based upon tests believed to be reliable and practical field experience. The reader is cautioned, however, that Eagle Performance Plastics, Inc. cannot guarantee the accuracy or completeness of this information, and it is the customer's responsibility to determine the suitability of specific products in any given application.