

<b>UHMW Available Options</b>			
<b>Material</b>	<b>FDA/USDA</b>	<b>Description</b>	<b>Color Options</b>
Virgin	Yes	Standard UHMW	Natural and Various Colors
Reprocessed	No	Cost effective, recycled/repurposed UHMW	Black and Green
Crosslinked (XL)	No	Improved wear and reduced thermal expansion	Grey
GlassFilled	No	Advanced wear resistance and dimensional stability	Blue and Black
Dry Lubricated/Wax	Yes	Dry lubricants added to reduce coefficient of friction	Grey
Oil Filled	Yes	Reduced coefficient of friction	Grey
UV Stabilized	No	Extended life in outdoor applications	Black and Green
Anti-Static	Yes	Electrically conductive to reduce static buildup	Black
Flame Retartant	No	MSHA accepted for underground mining	White
Metal Detectable	Yes	Additives make it metal detectable	Blue
X-Ray Detectable	Yes	Additives make it x-ray detectable	Blue
Lub-X C	Yes	Increased sliding properties and eliminates slip-stick	Blue/Grey
Lub-X CV	Yes	Increased sliding properties, eliminates slip-stick, and high PV	Blue
High Temperature	Yes	Increased continuous use temperature	Natural and Various Colors

The data stated are typical values intended for reference and comparison purposes only. The data should not be used as a basis for design specifications or quality control. The information is provided as a guide to the best of our knowledge and given without obligation or liability. Testing under individual application circumstances is recommended.